


Cable and pulleys , gastight level indicator SFA/E



- For storage tanks
- Gastight indicator
- Protection from emitted vapors
- Works without power supply
- Options: Level switches; Graduated ruler

APPLICATIONS

- Liquid storage (neutral, acidic or basic)

DESCRIPTION

The SFA/E shows the level in a sealed storage tank. The equipment is designed for liquids that emit harmful or corrosive vapors, or to protect the stored liquid from external atmosphere.

The float, suspended to a rope (or cable) supported by 2 pulleys, drives a counterweight inside the guide tube, showing the level of the liquid. The pulleys are enclosed in PVC elbows with a no-jump system, thus ensuring perfect guidance of the rope. Elbows are connected together with a PVC transfer tube. The counterweight is guided in a tube \varnothing 63 mm, tightly closed. The equipment fits on the tank with a loose flange ND100 in PVC (Sized as PN10/16)

The guide tube is fixed through collars, and can support a PVC graduated ruler and/or level switches actuated by the magnetic counter weight (see data-sheet 583-03).

CODE NUMBERS AND REFERENCES

Code 583701

Reference SFA/E/M

Modular set comprising the following elements:

- 5 m long rope, PP, \varnothing 3 mm
- 1 Float, PPH, \varnothing 98 mm (S.G. min. 0.94)
- 1 Magnetic counterweight, PVC, \varnothing 50 mm, for tube \varnothing 63 x 57 mm
- 2 Gastight pulleys
- 2 Transfer tubes, PVC, \varnothing 40 mm, 1 m long (each)
- 1 Loose flange, PVC, ND100 with fitting device to tank
- 1 Bottom tap for guide tube (not included, comes with guide tube)
- Union couplings

Guide tube not included: to order separately at proper length

Code 583 720

Reference Kit SFA/E

Set comprising the following elements:

- 5 m long rope, PP, \varnothing 3mm
- 1 Float, PPH, \varnothing 98 mm (S.G. min. 0.94)
- 1 Magnetic counterweight, PVC, \varnothing 50 mm, for tube \varnothing 63 x 57 mm
- 2 Gastight pulleys

Code 583 570

Reference TT/SFA

Guide tube, transparent PVC, \varnothing 63 mm

Length to confirm on inquiry and purchase order

In order to facilitate handling during assembly and respect of carrier rules, the guide tube as well as the graduated scale (optional) can be made in several parts.

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Cable and pulleys , gastight
level indicator
SFA/E

08-02-2022

D-583.02-EN-AD

NIV

583-02/1