

Compact overflow detector MAXIMAT CX



- All-plastic versions
- Integrated transmitter and connection for test button
- No moving parts
- For storage tanks
- NPN / PNP interface

AGREEMENTS

- General building supervisory approval issued by DIBt: Z-65.13-494
- Certification of Product Approval by SVTI ASIT: KVU-Nr. 302.019.19
- Vlarex II (Corcon bvba) certificate: CP0914/3072-HCC001
- GOST-Clearance Certificate: 42 1300/ 9026 10 290 0

APPLICATION

Overflow detector in accordance with the German Water Resources Act (WHG) for containers used for storing, filling and handling water-polluting, electrically conductive, non-flammable liquids.

DESCRIPTION

MAXIMAT CX compact overflow detectors are level limit switches which are used to prevent overflowing of containers with water polluting liquids. When an electrically conductive liquid comes into contact with the detector stem, the integrated electronics respond by interrupting the continuous output signal. This signal can be read out from the system controller as an acoustic and optical alarms and, if required, can be used to cause an emergency shutdown of the filling process.

TECHNICAL FEATURES


Detection	Capacitive high-frequency sensor, fail-safe detector
Ambient temperature	-20 ... +60 °C
Operating pressure	Atmospheric; Limits: 0.8 to 1.1 bar
Housing head	PBT, fibre-glass reinforced
Protection	IP65 according to EN 60 529
Fittings	See the table "ordering information"
Power supply	15 ... 27 V DC
Consumption	< 1 W
Outputs	Potential-free Reed contact for low voltage (Normally Closed, it opens when alarm occurs) Rated: Max. 50 V AC / DC, Max. 0.5 A, Max. 10 VA, convenient for operating with a coupling relay or PLC, signaling device TC4 / TC1 or CST unit. 2-wire alarm output reporting with transmitter MAXIMAT SHR C

Note: Simultaneous use of both outputs is not possible.

Terminals	Screw terminals, cable max. 2.5 mm ²
Additional function	Connection of an external test button (potential-free contact), for a complete diagnostic of the device integrity (connection loops, electronics).

Connection options	Alarm units: MAXIMAT TC1 / TC4 Coupling relay: CST Transmitter: MAXIMAT SHR C Automation with PLC
--------------------	--

WHG



BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL
Tel +33 (0)1 30 25 83 20 Web www.bamo.eu
Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Compact overflow detector MAXIMAT CX

16-10-2019

D-556.06-EN-AC

LEV

556-06 /1

TECHNICAL FEATURES (continued)

EC Conformity: The instrument meets the legal requirements of the current European Directives.

ORDERING INFORMATION

Compact overfill detector MAXIMAT CX

- 20** Stem O.D. 20mm
- 40** Stem O.D. 40mm

- K** with connection head
- 0** without connection head

Materials

- 4** PE (Standard)
- 2** PP (on request)
- 3** PVDF (on request)

Trigger point

- V** Adjustable
- N** Fixed point

Fittings

- U2** CX40: BSP 2" sleeve nut for weld-on union (V type)
- U254** CX40: BSP 2" sleeve nut for PE weld-on union (V type)
- U252** CX40: BSP 2" sleeve nut for PP weld-on union (V type)
- U253** CX40: BSP 2" sleeve nut for PVDF weld-on union (V type)
- G2** CX40: BSP 2" process interface, external thread (N & V types)
- F40** CX40: Flange DN 40, PN 10 (N & V types)
- F50** CX40: Flange DN 50, PN 10 (N & V types)
- G1** CX20: BSP 1" process interface, external thread (N & V types)
- G11/4** CX20: BSP 1 1/4" process interface, external thread (V type)
- G11/2** CX20: BSP 1 1/2" process interface, external thread (V type)
- F25** CX20: Flange DN 25, PN 10 (V type)
- F32** CX20: Flange DN 32, PN 10 (V type)

Fitting materials

- 1** PVC (Standard)
- 4** PE
- 2** PP
- 3** PVDF

L Distance (mm), from sealing surface *

MAXIMAT CX

Other versions: On request.

Please contact us.

- (V): Adjustable process connection (Adjustable trigger point distance)
- (N): Not adjustable process connection (Fixed trigger point distance)

Note:

Not all materials can be combined with each other; This applies for all non-adjustable versions on above table.

The overall length of the stem is 50 mm longer than the distance "L" plus, the height of the adjusting threaded fitting. During commissioning, the triggering level "A" can be adjusted by 50 mm downwards (i.e. lower switching point). Distance "L" is the desired trigger point measured as of the sealing surface.

* Min. installation length for O.D. 40 and 20 mm versions = 150 mm

* Max. installation length for O.D. 40 mm versions = 1000 mm

* Max. installation length for O.D. 20 mm versions = 500 mm

Larger lengths and version with double cable gland: On request.

BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Compact overfill detector
MAXIMAT CX

16-10-2019

D-556.06-EN-AC

LEV

556-06/2


ORDERING INFORMATION (continued)

Standard versions

Code	Reference	Description
556 602	MAXIMAT CX 40 K 4 V G2 1 L= 200mm	Terminal housing, O.D. 40 mm, PE, adjustable, BSP 2" PVC, L = 200mm
556 604	MAXIMAT CX 40 K 4 V G2 1 L= 300mm	Terminal housing, O.D. 40 mm, PE, adjustable, BSP 2" PVC, L = 300mm
556 606	MAXIMAT CX 40 K 4 V G2 1 L= 400mm	Terminal housing, O.D. 40 mm, PE, adjustable, BSP 2" PVC, L = 400mm
556 608	MAXIMAT CX 40 K 4 V G2 1 L= 500mm	Terminal housing, O.D. 40 mm, PE, adjustable, BSP 2" PVC, L = 500mm
556 662	MAXIMAT CX 20 K 4 V G1 1 L= 200mm	Terminal housing, O.D. 20 mm, PE, adjustable, BSP 1" PVC, L = 200mm
556 664	MAXIMAT CX 20 K 4 V G1 1 L= 300mm	Terminal housing, O.D. 20 mm, PE, adjustable, BSP 1" PVC, L = 300mm
556 666	MAXIMAT CX 20 K 4 V G1 1 L= 400mm	Terminal housing, O.D. 20 mm, PE, adjustable, BSP 1" PVC, L = 400mm
556 668	MAXIMAT CX 20 K 4 V G1 1 L= 500mm	Terminal housing, O.D. 20 mm, PE, adjustable, BSP 1" PVC, L = 500mm

DIMENSIONS

Examples of common models



BAMO INTERNATIONAL

22, Rue de la Voie des Bans · Z.I. de la gare · 95100 ARGENTEUIL

Tel +33 (0)1 30 25 83 20 Web www.bamo.eu

Fax +33 (0)1 34 10 16 05 E-mail export@bamo.fr

Compact overfill detector
MAXIMAT CX

16-10-2019

D-556.06-EN-AC

LEV

556-06/3