

Delta Skimmer

VIKOMA

Protecting our environment over 50 years



Quality
Reliability
Innovation



A self contained free floating oil recovery system for shallow water

- Simple and easy to use
- Ideal for use in shallow water and confined spaces
- A robust, lightweight, maintenance free floating suction head
- Includes hose floats

For more information please contact us

Tel: +44(0)1983 200560

www.vikoma.com

sales@vikoma.com

Vikoma Delta Skimmer has seven inlet ports around the semicircular head and strong suction to give a 180° recovery zone. The skimmer can recover up to 24m³ per hour.

The Delta has no moving parts and so requires virtually no maintenance, and it is simple and quick to deploy and can be easily operated by an unskilled operator.

The Vikoma Delta skimmer head can operate in as little as 7cm (2.75 inches) of water. The lightweight construction makes it particularly valuable for beach clean-up, shoreline operations, around piers and jetties, as well as in lakes, ponds, ports, harbours, rivers and inland waters. The compact design also allows the system to operate in holding tanks and storm water pits. In fact, the Delta Skimmer system is suitable for use in any calm water requiring the rapid removal of oils or other floating contaminants.

The Delta head buoyancy pockets are filled with closed cell foam to maintain level flotation if the outer case is damaged.

The powerful VikoPump is rated at 24m³ and will handle a full range of contaminants. The VikoPump has remarkable suction capabilities, can self prime and can also run dry for short periods. This flexibility means that it can be used for other duties such as tanker loading, drainage duties or anywhere there is a requirement to transfer liquid.

The Delta skimmer system has been used around the world and has proven to offer extremely high reliability with very low maintenance.

The systems comprises of a suction weir skimmer head coupled to a diesel driven VikoPump with associated hoses, couplings and floats.

Product Benefits:

- Ideal for shallow waters and confined spaces
- Simple to operate suction weir skimmer
- 24m³ per hour recovery rate



Delta System



Delta Head



Maximum Recovery Capacity
24m ³ per hour
System components
Vikoma Delta Skimmer Head. Diesel driven V164D Transfer Pump with spark arrestor and Automatic Overspeed Shutdown. Hose Kit.
Optional extras
Spares Kit Hose Adaptor for Mini Pump

