

Smart-Up  
LockLeak  
Proof Seal

Non-toxic



Recyclable



Durable

Chemically  
Resistant

Oil-resistant

Temperature  
Resistant

-30 °C/+70 °C



# Folding Spill Containment Berm

## INDUSTRY 280

1200 × 1200 × 200

Versatile, on-the-go spill containment berm for emergency spill response and for capturing dangerous leaks from barrels, drums, kegs, IBC containers, tanks, etc. Easily portable and quickly assembled without the use of tools. The special Smart-Up Lock system of wall supports allows for immediate folding of the sides for convenient manipulation inside the berm or for limited vehicles drive in/out. Ideal for use in industrial halls, etc.

**Mechanically resistant containment berm for emergency spill response or for safe storage of drums and barrels with hazardous substances**



- ▶ Highly mechanically resistant recyclable ReccoPro HardGuard material – abrasion and puncture resistance
- ▶ Fast and easy set up without tools
- ▶ Smart-Up Lock wall support folding system for quick folding and positioning of the berm sides
- ▶ Patented method of securing corners – Leak Proof Seal screws with a seal - prevents leakage even when the berm is filled to full capacity
- ▶ Wall supports with integrated holes for anchoring the berm to the floor
- ▶ The safe design of the berm and wall supports provides unobstructed work space, allows free and safe movement of people, equipment and vehicles inside and outside the berm – protection against tripping or falling
- ▶ Foldable design and space-saving packaging save storage space and make transportation easier





Possibility to fold any side of the berm



Easy handling inside the berm thanks to the Smart-Up Lock system of folding wall supports



In case of damage, the Smart-Up Lock wall supports can be easily and quickly replaced

Easy maintenance of the berm thanks to the possibility of simple corner layout

Leak Proof Seal screws with seals prevent liquid leakage even when the berm is filled to the maximum with liquid



## Technical details

The INDUSTRY foldable spill containment berm is made of durable recyclable ReccoPro HardGuard material with high mechanical and chemical resistance. The containment berm is supplied with dismantled wall supports, which minimizes the size of the package when the berm is not in use and allows for more comfortable and less physically demanding handling. Additional installation of the wall supports is very fast, smooth and without the use of tools. The Smart-Up Lock system of the wall supports ensures lightning-fast positioning of the sidewalls to a 90° vertical position and equally fast folding to a horizontal position, which allows for comfortable drive-in and out, exit and manipulation inside the berm. The supports prevent sagging of the sides and are equipped with holes for anchoring to the ground under high wind conditions. The wall supports fold down in only one way, inward towards the inside of the berm. The special Leak Proof Seal system of locking the corners of the berm with screws with a seal prevents leakage during full containment for fluid-tight reliability. The temperature range of use of the spill containment berm is -30 °C to +70 °C. The berm is available in several dimensional variants.



### Smart-Up Lock wall supports folding system

Smart-Up Lock is a patented design system of folding wall supports that can be locked in a 90° vertical position with one movement. This system allows for the same quick and easy folding back to a horizontal position for convenient and easy drive-in and out or handling equipment into the berm. The folding wall supports also have integrated holes for anchoring the berm to the ground in the event of strong winds or other pressure on the side of the berm. In case of damage, the wall supports can be easily and quickly replaced.



### Leak Proof Seal screws

The corner construction secured in the upper part of the berm with special Leak Proof Seal screws with a seal ensures 100% protection against leakage even when the berm is filled to the maximum with liquid.

Code	Name	Dimensions (mm)	Packaging dimensions (mm)	Volume (l)	Weight (kg)	Material	Colour
7309	Industry 280	1200 × 1200 × 200	750 × 600 × 200	280	7	ReccoPro HardGuard 61	blue/black



# Dimensional variants of ReccoPro Smart-Up Lock Folding Spill Containment Berms



Smart-Up Lock



Leak Proof Seal



Non-toxic



Recyclable



Durable



Chemically Resistant



Oil-resistant



Temperature Resistant  
-30 °C / +70 °C



Code	Name	Material	Volume (l)	Dimensions (mm)
007309	INDUSTRY 280	HardGuard 61	280	1200 × 1200 × 200
007310	INDUSTRY 420	HardGuard 61	420	1800 × 1200 × 200
007311	INDUSTRY 570	HardGuard 61	570	2400 × 1200 × 200
007301	INDUSTRY 640	HardGuard 61	640	1800 × 1200 × 300
007302	INDUSTRY 960	HardGuard 61	960	1800 × 1800 × 300
007312	INDUSTRY 1140	HardGuard 61	1140	2400 × 2400 × 200
007303	INDUSTRY 1280	HardGuard 61	1280	2400 × 1800 × 300
007304	INDUSTRY 1500	HardGuard 61	1500	2800 × 1800 × 300
007320	IBC 1	HardGuard 91	1200	2160 × 1600 × 350
007321	IBC 2	HardGuard 91	1800	2600 × 2000 × 350
007322	IBC 4	HardGuard 91	2720	4600 × 1700 × 350
007323	IBC 6	HardGuard 91	4000	3600 × 3200 × 350
007324	IBC 8	HardGuard 91	5360	4820 × 3200 × 350
007325	IBC 10	HardGuard 91	7210	6100 × 3400 × 350
007314	DRIVE THROUGH 2140	HardGuard 91	2140	3000 × 2400 × 300
007305	DRIVE THROUGH 2680	HardGuard 91	2680	3000 × 3000 × 300
007315	DRIVE THROUGH 4110	HardGuard 91	4110	4600 × 3000 × 300
007306	DRIVE THROUGH 5400	HardGuard 91	5400	4900 × 3700 × 300
007307	DRIVE THROUGH 7150	HardGuard 91	7150	4900 × 4900 × 300
007316	DRIVE THROUGH 9370	HardGuard 91	9370	8500 × 3700 × 300
007308	DRIVE THROUGH 11080	HardGuard 91	11080	6100 × 6100 × 300
007317	DRIVE THROUGH 16750	HardGuard 91	16750	15200 × 3700 × 300
007318	DRIVE THROUGH 18190	HardGuard 91	18190	16500 × 3700 × 300
007319	DRIVE THROUGH 21910	HardGuard 91	21910	17100 × 4300 × 300

INDUSTRY

IBC

DRIVE THROUGH

